

Rail Mounted Terminal Blocks » Polyamide Range Of Terminals

Select Terminal Series :

► Feed Through Terminal



elmex "K" Series Universal (TS35mm & TS32mm) DIN Rail Mounted **Feed Through Terminals** in Polyamide 66 Housing offers the complete range suitable for all control and power application. The proven screw clamp design offers high contact force and is easy to use. The range covers terminals for conductor sizes from 0.5 sq mm to 95 sq mm. The special foot design provides the slot for easy mounting and removal of a single terminal from the stack, using a screwdriver.

FEED THROUGH



SPRING LOADED FEED THROUGH



elmex Spring Loaded Terminals employ compression springs below the contact clamp assembly, for better and more reliable connection for high vibration applications.

<p>KUTM 2.5</p>  <p>CE</p> <p>IEC : 800 V 24 A 2.5 sq mm 0.5 Nm UL : 600 V 25 A 20 AWG - 12 AWG 7 Lbln</p> <p>Height : 41 mm (1.60 Inch) Width : 42.5 mm (1.66 Inch) Pitch : 5 mm (0.20 Inch)</p>	<p>KUT 2.5</p>  <p>UL CE Ex</p> <p>IEC : 800 V 24 A 2.5 sq mm 0.5 Nm UL : 600 V 25 A 20 AWG - 12 AWG 7 Lbln</p> <p>Height : 41 mm (1.60 Inch) Width : 42.5 mm (1.66 Inch) Pitch : 6 mm (0.23 Inch)</p>	<p>KUT 4</p>  <p>UL CE S FI ND Ex</p> <p>IEC : 800 V 32 A 4 sq mm 0.5 Nm UL : 600 V 35 A 20 AWG - 10 AWG 7 Lbln</p> <p>Height : 46.4 mm (1.81 Inch) Width : 42.5 mm (1.66 Inch) Pitch : 6.7 mm (0.26 Inch)</p>
<p>KUT 6</p>  <p>UL CE S FI ND Ex</p> <p>IEC : 800 V 41 A 6 sq mm 0.8 Nm UL : 600 V 50 A 20 AWG - 8 AWG 14 Lbln</p> <p>Height : 46.4 mm (1.81 Inch) Width : 42.5 mm (1.66 Inch) Pitch : 8 mm (0.31 Inch)</p>	<p>KUT 10</p>  <p>UL CE S FI ND Ex</p> <p>IEC : 800 V 57 A 10 sq mm 1.2 Nm UL : 600 V 65 A 16 AWG - 6 AWG 14 Lbln</p> <p>Height : 46.4 mm (1.81 Inch) Width : 42.5 mm (1.66 Inch) Pitch : 10 mm (0.39 Inch)</p>	<p>KUT 16</p>  <p>UL CE S FI ND Ex</p> <p>IEC : 800 V 76 A 16 sq mm 1.2 Nm UL : 600 V 100 A 12 AWG - 3 AWG 17 Lbln</p> <p>Height : 52 mm (2.03 Inch) Width : 44.5 mm (1.74 Inch) Pitch : 12 mm (0.47 Inch)</p>
<p>KUT 25</p>  <p>UL CE S FI ND Ex</p> <p>IEC : 1000 V 101 A 25 sq mm 2.3 Nm UL : 600 V 115 A 10 AWG - 2 AWG 20 Lbln</p> <p>Height : 56 mm (2.18 Inch) Width : 45 mm (1.76 Inch) Pitch : 12 mm (0.47 Inch)</p>	<p>KUT 35</p>  <p>UL CE S FI ND Ex</p> <p>IEC : 1000 V 125 A 35 sq mm 3 Nm UL : 600 V 130 A 14 AWG - 1 AWG 38 Lbln</p> <p>Height : 58 mm (2.26 Inch) Width : 51 mm (1.99 Inch) Pitch : 17 mm (0.66 Inch)</p>	<p>KUT 50</p>  <p>UL CE S FI ND Ex</p> <p>IEC : 1000 V 150 A 50 sq mm 8 Nm UL : 600 V 150 A 6 AWG - 2/0 AWG 60 Lbln</p> <p>Height : 75.5 mm (2.94 Inch) Width : 71 mm (2.77 Inch) Pitch : 20.5 mm (0.80 Inch)</p>
<p>KUT 95</p>  <p>UL CE S FI ND Ex</p> <p>IEC : 1000 V 232 A 95 sq mm 20 Nm UL : 600 V 230 A 2 AWG - 4/0 AWG 160 Lbln</p> <p>Height : 90.5 mm (3.53 Inch) Width : 83 mm (3.24 Inch) Pitch : 25 mm (0.98 Inch)</p>	<p>KUT4 - 1x2</p>  <p>CE</p> <p>IEC : 1000 V 32 A 4 sq mm 0.5 Nm</p> <p>Height : 53 mm (2.07 Inch) Width : 47 mm (1.83 Inch) Pitch : 6 mm (0.23 Inch)</p>	<p>KUT4 - 2x2</p>  <p>CE</p> <p>IEC : 800 V 24 A 4 sq mm 0.5 Nm</p> <p>Height : 53 mm (2.07 Inch) Width : 67 mm (2.61 Inch) Pitch : 6 mm (0.23 Inch)</p>